

Addl. PCCF, MoEFCC, Regional Office (ECZ), Bungalow No. A-2, Shyamali Colony, Ranchi – 834002.

Ref No. - JMB/115/ 001570

/2017

November, 22, 2017

SUB: Half Yearly Compliance Report of the conditions of EC issued by MoEFCC, New Delhi to Jamadoba Coal washery, Tata Steel Limited, Dhanbad for the period April'17 to September'17.

Dear Sir,

We are enclosing herewith compliance report for the period April'17 to September'17 for the EC granted vide letter no.- J-11015/203/2011-IA.II(M) dated- 3rd March 2014 issued by Ministry of Environment, Forest and Climate Change, New Delhi. This is for your kind perusal.

Thanking you,

Yours faithfully,

General Manager (Coal)

Email I.D.- skumar.singh@tatasteel.com

Encl: As above.

Copy to: Member Secretary, Eastern Zonal Office, Southend Conclave, 502, 5th Floor 1582,

Rajdanga Main Road, Kolkata-700107.

Copy to: Member Secretary, JSPCB, T.A. Division Building (Ground Floor), H.E.C, Dhurwa,

Ranchi -834004.

TATA STEEL LIMITED

HALF YEARLY COMPLIANCE REPORT

(PERIOD: APRIL'17 – SEPTEMBER'17)

JAMADOBA COAL WASHERY

(CAPACITY: EXPANSION FROM 1 TO 2 MTPA RAW COAL THROUGHPUT) TEHSIL: JHARIA, DIST: DHANBAD, JHARKHAND



TATA STEEL LIMITED, JHARIA DIVISION

P.O.- JAMADOBA, DIST. - DHANBAD, STATE- JHARKHAND, PIN CODE – 828112.

ENVIRONMENTAL CLEARANCE GRANTED VIDE LETTER NO. - J-11015/203/2011-IA.II(M) DATED- 03.03.2014 ISSUED BY GOVT. OF INDIA, MINISTRY OF ENVIRONMENT, FOREST AND CLIMATE CHANGE, NEW DELHI.

S. No.	Condition	Compliance Status		
Specific (Condition			
(i)	Adequate green belt shall be provided around coal handling and other areas.	Greenery has been developed in many areas around the washery premises. Now a comprehensive green belt development plan to cover the entire washery campus area has being outlined. The expansion work is still in progress and is expected to be completed by June'2018. Therefore the plantation activities will be initiated from next year monsoons only as plant survival rate could be affected during construction phase.		
(ii)	Action plan be developed and implemented for abandoned tailing ponds and for their restoration to the original land use.	since the washery expansion is yet to		
(iii)	Fly ash generated from the captive power plant of the washery be utilized for house construction, roads and such uses, strictly complying to the timeline in the EIA Notification, 2006 and maintaining proper records.	This is not applicable as we have ceased the operation of our captive Jamadoba power plansince April'15.		
(iv)	No use of fly ash with sand will take place for stowing in underground mines.	This will be strictly followed for our captive underground mines.		
(v)	Transportation of fly ash to be done properly by mechanically covered trucks.	This is not applicable as there is no fly ash being generated since April'15.		
(vi)	The proponent shall connect all the villages in the leasehold area with water pipeline connection.	All the villages in the leasehold areas will be supplied safe drinking water through pipeline connection. A network of more than 22000 metres of pipeline connection has been established along with 33 water tanks (capacity of 4500 litres).		

Ye.

(vii)	The proponent shall expedite and implement the pilot plant to convert mine water into drinking/domestic water to supply the same to the population of Dhanbad and surrounding areas and shall continue to carry out this activity.	Mine water is already being converted into potable water by Tata Steel in our 4 nos. Water Treatments Plants (located at Jamadoba, Digwadih, Bhelatand and Malkera having cumulative capacity of around 8000 KL/D). The treated water is then supplied to our colonies and leasehold villages. This will continue in future too.
(viii)	Tanks/ponds shall be regularly cleaned and maintained. Plantation activities shall be intensified in the mine areas.	Tanks/ ponds are regularly cleaned and maintained by TSRDS. Some of the glimpses of the activities are shown below. Plantation activities are undertaken every year in the barren mine leasehold areas. Further, TSRDS engages with the villagers for plantation in the village lands. In FY18, total 4 nos of ponds were renovated, 2 nos. of new ponds have been constructed in Jamadoba area.
(ix)	The proponent shall expedite the activities undertaken by TSRDS in over 30 villages in the leasehold area over 15000 households covering a population of about 1.4 lakh.	CSR activities of TSRDS are managed by a team of experts who are dedicatedly involved in providing benefits and improving standard of living in over 30 villages. The list of activities are developed in consultation with the village

P

		representatives and implemented in a time- bound manner.
(x)	CSR activities of TSRDS are managed by a team of experts who are dedicatedly involved in providing benefits and improving standard of living in over 30 villages. The list of activities are developed in consultation with the village representatives and implemented in a time-bound manner.	The proposed CSR expenditure for the entire company is decided as per the new Company Rules. Once the CSR budget for company is fixed, a share of that amount is dedicated and utilized for implementing the CSR activities at our Jharia Division level. The CSR expenditure for FY17 is Rs.4.29 crores.
(xi)	Cost for additional environmental protection measures shall be not less than Rs. 503.00 lakhs. The status of implementation including costs incurred shall be regularly reported to this Ministry and its respective Regional Office in the region as part of the compliance report and also uploaded on the company website.	The status of implementation of environmental protection measures including costs will be regularly submitted once the expansion job for washery is completed. It will also be uploaded on company website as part of compliance report. The regular expenditure incurred for environment protection and management are mentioned in Point no. xii of General Condition.
(xii)	The slope of the embankment towards the river shall be at least 1:3 for stability and shall be stabilized with plantation using native species selected from the study area.	The washery is about 1.5 kms away from the Damodar River. Hence it is not applicable.
(xiii)	Top soil shall be stored in the earmarked area and used within a year of its generation for green belt development and for plantation/reclamation.	There are no top soil dumps hence it is not applicable.
(xiv)	No external OB dump shall be created for the expansion project. Monitoring and management of existing reclaimed dumpsites shall continue until the vegetation becomes self-sustaining. Compliance status shall be submitted to the Ministry of Environment & Forests and its respective Regional Office on yearly basis.	Not applicable as this is a washery project.

12

(xv)	Catch drains and siltation ponds of appropriate size shall be constructed to arrest silt and sediment flows from soil, OB and mineral dumps. The water so collected shall be utilised for watering the mine area, roads, green belt development, etc. The drains shall be regularly desilted and maintained properly.	There are no soil or OB dumps in the washery premises. Only the by-products are stored in the stockyards located in the washery premises which are sold off within a week.
(xvi)	Garland drains (size, gradient and length) and sump capacity shall be designed keeping 50% safety margin over and above the peak sudden rainfall and maximum discharge in the area adjoining the mine site. Sump capacity shall also provide adequate retention period to allow proper settling of silt material.	Garland drains of adequate size and gradient already exist around the washery area to channelize the surface runoff. The runoff is diverted to the tailing ponds and clear water is utilized in the washery. It will be further strengthened under washery expansion jobs.
(xvii)	Dimension of the retaining wall at the toe of the dumps and OB benches within the mine to check run-off and siltation shall be based on the rainfall data.	Not applicable as we do not have any opencast mines.
(xviii)	Crushers at the CHP shall be operated with high efficiency bag filters/water sprinkling system shall be provided to check fugitive emissions from crushing operations, conveyor system which shall be closed, haulage roads, transfer points, etc.	The following measures have been implemented: i) Dry-fog system at all transfer points of CHP. ii) Enclosures around crushers. iii) Belts have been covered on top and both sides. These arrangements will protect the coal mass moving on belt from blowing wind. In this way the dust generation would be minimized. iv) Fixed water sprinklers on the haulage roads.
(xix)	Drills shall be wet operated only.	Not applicable.
(xx)	Controlled blasting shall be practiced with use of delay detonators and only during daytime. The mitigative measures for control of ground vibrations and to arrest the fly rocks and boulders shall be implemented.	Not applicable.

(xxi)	The Washery shall be a zero-discharge and no wastewater shall be discharged from the washery into the drains/natural watercourses. No groundwater shall be used for washery operations. Recycled water shall be used for development and maintenance of green belt and in the plant operations.	Washery is already operating on a zero-discharge principle. No waste-water is discharged into the drains/ natural water systems. Only mine water is utilized for the washery operations as make up water requirement. The recycled water is again used for plant operations and green-belt development.
(xxii)	The raw coal, washed coal and middling and coal wastes (rejects) shall be stacked properly at earmarked site(s) within sheds/stockyards fitted with wind breakers/shields. Adequate measures shall be taken to ensure that the stored minerals do not catch fire. The storage period shall be not more than 2-3 days.	The material is being stacked properly at stockyards located within the washery. We have a well-established system for disposal of rejects/tailings to consumers so that storage period is not more than 2-3 days.
(xxiii)	The proponent shall maintain proper records of the ash content of raw (ROM) coal, clean coal, middling and coal rejects along with quantum of raw coal obtained and washed and dispatched every month and the same shall be uploaded on the company website every month.	Proper records are already maintained and being uploaded on the company website every month. The records are attached here as Annexure V.
(xxiv)	All internal roads shall be concreted or black topped and the approach roads used for the project shall be blacked topped. Facilities for parking of trucks carrying raw coal from the linked coalmines shall be created within the Unit.	All the internal roads have been concreted while the approach roads are black-topped. There is a facility for parking of trucks within the unit.
(xxv)	Roads used for coal transportation to the linked DRI/TPP shall be developed with 3-tier avenue plantation using a mix of native species. The trucks used for coal transportation shall be high capacity trucks. Drivers of trucks for coal transportation shall be engaged based on past records of road safety and compliance of safety regulations and shall be suitably sensitized about road safety and maintenance of vehicles to keep vehicular emissions to be within	There is no linked DRI/TPP. - Raw coal is received via underground coal conveyor belt network and therefore no truck transportation of coal is involved. - Clean coal is dispatched via rail from the Railyard situated on the washery premises. The clean coal is kept in storage bins and directly transferred to the rail wagons through covered coal-conveying system. - As for the trucks moving within the washery,

	,	
	prescribed limits.	utilized for shifting of tailings and rejects to storage yard, all the given provisions related to road safety and driver competence are being strictly complied with.
(xxvi)	The roads (internal/approach and roads used for the project) shall be regularly cleaned with mechanical sweepers and with water sprinklers. A 3-tier avenue plantation shall be developed along the major approach roads, internal roads and nearby roads used by the company.	Fixed Water sprinklers have already been installed in the washery premises. Plantation along the road-side is done wherever feasible. A three-tier green belt will be developed along the boundary of washery during the next monsoon period as construction activity job is still going on.
(xxvii)	Green belt shall be developed along the areas such as the washery unit, crushing unit, and stockyards and at transfer points and in between mine operations and habitations.	Greenery has been developed in many areas around the washery premises. Green belt will be developed along the boundary of washery during the next monsoon period.
(xxviii)	Hoppers of the coal crushing unit at the crushing shed and washery unit shall be fitted with high efficiency bag filters/Dust extractors and mist spray water sprinkling system shall be installed and operated effectively at all times of operation to check fugitive emissions from crushing operations, transfer points of belt conveyor systems which shall be closed and from transportation roads.	Dry-fog system has been already installed to suppress the dust generated at CHP and transfer points of belt conveyor systems. Fixed-type water sprinklers are also installed on the internal roads of the washery. These are operated effectively at all times to check the fugitive emissions. Fugitive dust emission monitoring is done on half-yearly basis. The values are within the stipulated norms.
(xxix)	The proponent shall ensure that coal such as stones, shale and other wastes of an ash content of 77% or more only shall be dumped into the mine voids. Coal rejects with an ash content of 76% or less shall be fully utilized for power generation in linked TPP.	It is being followed.
(xxx)	Regular monitoring of groundwater level and quality including levels of heavy metals such as Hg, Cd, Cr, Se, etc shall be carried out by establishing a network of existing wells and construction of new peizometers. The monitoring for quantity and quality of ground water as per IS:	The monitoring of groundwater level and quality is done four times a year. The groundwater quality report & groundwater level for premonsoon (May) and monsoon (August) are provided in Annexure-I. The monitoring of heavy metals such as Hg, Cd,

	10500 shall be done four times a year in pre-monsoon (May), monsoon (August), post-monsoon (November) and winter (January) seasons. Proper records of the data thus collected shall be maintained submitted to the Ministry of Environment & Forests and to the Central Pollution Control Board quarterly within one month of monitoring.	Cr, Se, etc in the groundwater was done during the hydro-geological study conducted by Indian School of Mines, Dhanbad. Data has been provided in previous compliance reports.
	As the entire mine water is proposed to be used for the mine-cum-washery operations, measures shall be taken for recharging ground water in and around the mine in the study area. A Plan for water conservation and recharge measures of ground water along with	More than 50% of the water pumped out during underground mining activity is re-circulated back into the mine for the purpose of stowing. Backfilling of mine voids by stowing is done using sand which is having the porosity to hold the underground water thus helping aquifer to retain the underground water.
(xxxi)	budgetary provisions be prepared and implemented in consultation with the Central/State Ground Water Board to mitigate the adverse impact of mining which may lead to depletion of ground water in the area. The Company shall put up artificial groundwater recharge measures for augmentation of groundwater resource in case monitoring of groundwater levels indicate decline of water table. Any additional water requirement for mining operation shall be met from rainwater use only. The project authorities shall meet water requirement of nearby village(s) in case the village wells go dry due to dewatering of mine.	Further, there are a number of ponds existing on the surface of the mining lease which act as natural reservoirs for recharging ground water. These ponds/ tanks are regularly cleaned and maintained by our CSR department. As per the hydro-geological report, the variation in the ground water level is only seasonal. The water requirement of the nearby villages is being met by the company already. Now piped drinking water is being provided.
(xxxii)	ETP shall also be provided for treatment of effluents from workshop, CHP and an STP shall be provided in the colony and the treated effluents shall be used for green belt development. Outflow of rainfall, if any, from the mine shall meet prescribed norms and the water quality of such discharge including levels of heavy metals such as Hg, Cd, Cr., Se, etc shall be monitored at the exit points and records maintained thereof and also uploaded on the company website. Online	No effluent is discharged outside of the washery. There is no separate workshop in the washery premises. A central workshop exists in Jamadoba Colliery with adequate Oil and Grease Trap. A Sewage Treatment Plant (STP) has been installed in one of the colonies of Jharia Division and its treated water used for gardening and other purpose. Other colonies will also be covered with STPs in the near future.

	monitoring equipment shall be installed by the proponent to ensure that the water quality parameters of mine water discharge are well within the General Discharge Standards under EP, Rules, 1986.	
(xxxiii)	Besides carrying out regular periodic health check-up of their workers, 10% of the workers identified from workforce engaged in active mining operations shall be subjected to health check-up for occupational diseases and hearing impairment, if any, through a recognised agency found in the district, and the results reported to this Ministry and to DGMS.	Not applicable. Though PME is done for washery workers periodically at our OH centre.
(xxxiv)	For monitoring land use pattern and for post mining land use, a time series of landuse maps, based on satellite imagery (on a scale of 1: 5000) of the core zone and buffer zone, from the start of the project until end of mine life shall be prepared once in 3 years (for any one particular season which is consistent in the time series), and the report submitted to MOEF and its concerned Regional Office in the region.	Not applicable as there is no proposed changes in land use and land cover due to washery.
(xxxv)	Land oustees shall be compensated as per the norms laid out R&R Policy of CIL or the National R&R Policy or R&R Policy of the State Government whichever is higher.	Not applicable
(xxxvi)	A Final Mine Closure Plan along with details of Corpus Fund shall be submitted to the Ministry of Environment & Forests five year before mine closure for approval. Habitat Restoration Plan of the mine area shall be carried out using a mix of native species found in the original ecosystem, which were conserved in-situ and ex-situ in an identified area within	Not applicable.

12

	the lease for reintroduction in the mine during mine reclamation and at the post mining stage for habitat restoration and for development of grasslands.	
	Corporate Environment Responsibility: a) The Company shall have a well laid down Environment Policy approved by the Board of Directors.	The Company already has an Environment Policy approved by the Managing Director and it addresses all the issues mentioned. Tata Steel Environmental Policy is attached as Annexure-IV.
(xxxvii)	b) The Environment Policy shall prescribe for standard operating process/procedures to bring into focus any infringements/deviation/violation of the environmental or forest norms/conditions. c) The hierarchical system or Administrative Order of the company to deal with environmental issues and for ensuring compliance with the environmental clearance conditions shall be furnished.	The status of adherence to the policy and compliance to Environmental laws and regulations is regularly discussed at higher levels. Any non-compliance noticed is corrected at divisional level. If any issue is beyond our control, it is brought to the notice of higher management.
	d) To have proper checks and balances, the company shall have a well laid down system of reporting of non-compliances/violations of environmental norms to the Board of Directors of the company and/or shareholders or stakeholders at large.	

В.	GENERAL CONDITIONS	
(i)	No change in mining technology and scope of working shall be made without prior approval of the Ministry of Environment and Forests.	The points mentioned in the EC letter will be strictly followed.
(ii)	No change in the calendar plan of production for quantum of mineral coal shall be made.	It will be strictly followed.
(iii)	Four ambient air quality monitoring stations shall be established in the core zone as well as in the buffer zone for PM10, PM2.5, SO2 and NOx monitoring. Location of the stations shall be decided based on the meteorological data, topographical features and environmentally and ecologically sensitive targets in consultation with the State Pollution Control Board. Monitoring of heavy metals such as Hg, As, Ni, Cd, Cr, etc carried out at least once in six months.	The Air quality monitoring stations are: (i)Jamadoba Group Office (Core Zone) (ii)New Village Colony, Jamadoba (Buffer Zone) (iii)Digwadih 12 No. Colony (Buffer Zone) (iv)6&7 Pits Kalimandir area (Buffer Zone) Monitoring of heavy metals in ambient air is being performed by an independent laboratory (recognised by MoEFCC) once in six months. The results are enclosed as Annexure-II.
(iv)	Data on ambient air quality (PM10, PM 2.5, SO2 and NOx) and heavy metals such as Hg, As, Ni, Cd, Cr and other monitoring data shall be regularly submitted to the Ministry including its concerned Regional Office and to the State Pollution Control Board and the Central Pollution Control Board once in six months. Random verification of samples through analysis from independent laboratories recognized under the EPA rules, 1986 shall be furnished as part of compliance report.	The state of the s

(v)	Adequate measures shall be taken for control of noise levels below 85 dBA in the work environment. Workers engaged in blasting and drilling operations, operation of HEMM, etc shall be	Regular noise survey is being conducted in the underground work environment. Workers are provided with ear-plugs/ muffs in high noise areas. The noise levels monitored in the month of September'17 is given below:					
	provided with ear plugs/muffs.	S .No.	Unit / Place	Equipment / Location	Distance (meter away)	Leq (dB 'A')	Exposure Hours
		1.		Main Plant Control Room	-	68.4	8 hrs. /Shift
		2		Screen floor, Stand – II vibrating Screen – 211# 1 to 211# 4	4 m.	80.5	2 hrs /Shift
		3		Dense pump pit Stand- I floor	2 m.	81.1	2 hrs /Shift
		4		Primary Magnetic Separator No- 1 & 2	2 m.	74.3	4 hrs /Shift
		5		Mixer Box Floor (Near Control Room Side)	2 m.	79.5	8 hrs ./Shift
		6 7 JCPP	Discharge Shute (Screen 215# 1)	2 m.	80.7	2 hrs /Shift	
			JCPP	Discharge Shute (Screen 215# 2)	2 m.	79.7	2 hrs /Shift
		8		PTS (Control Room)	-	69.0	8 hrs. /Shift
		9. 10. 11. 12. 13.		CHP (Control Room)	-	66.1	8 hrs. /Shift
				In front of Diesel & Loco Shed		78.4	4 hrs. /Shift
				Discharge of Conveyor-6 to Conveyor-1	2 m.	82.9	2 hrs. /Shift
				Centrifuge Section Screen bowl	-	82.7	8 hrs. /Shift
				Stand #2 crossover Bridge	4 m.	81.4	4 hrs. /Shift
(vi)	Industrial wastewater (workshop and wastewater from the mine) shall be properly collected, treated so as to conform to the standards prescribed under GSR 422 (E) dated 19th May 1993 and 31st December 1993 or as amended from time to time before discharge. Oil and grease trap shall be installed before discharge of workshop effluents.	was bacl wor grea	hery k for r kshop ase tra	e-water is dis premises. 100% re-use in the was and garage in Ja p has been provi	water hery. Th amadoba ded.	is received in the service of the se	a central re oil and
(vii)	Vehicular emissions shall be kept under control and regularly monitored. Vehicles used for transporting the mineral shall be covered with tarpaulins and optimally loaded.	are Coa from that tarp	being l trans n BCC only	vehicles having allowed to opera sportation throug CL mines till wa optimally load cover are allow	ite. gh truck shery ar ed truck	s is d nd it is	one only s ensured h proper

(viii)	Monitoring of environmental quality parameters shall be carried out through establishment of adequate number and type of pollution monitoring and analysis equipment in consultation with SPCB and data got analysed through a laboratory recognized under EP Rules, 1986.	We have a fully equipped Environment Cell Laboratory with qualified personnel. Laboratory has been recognized and registered with the Jharkhand State Pollution Control Board vide letter ref no. B-3922, dated-30.08.2012. The monitoring and analysis is also done at regular intervals by M/s S S Environics India Pvt. Ltd., an MoEF recognised laboratory (vide its notification 07.12.2012). We have also installed a Continuous Ambient Air Quality Monitoring Station at Jamadoba for real time monitoring with data transfer to JSPCB, Ranchi.
(ix)	Personnel working in dusty areas shall wear protective respiratory devices and they shall also be provided with adequate training and information on safety and health aspects.	Persons working in dusty area have been provided with dust masks & have been given awareness training on safety & health aspects. Regular PME (Periodic Medical Examinations) are being done.
(x)	Occupational health surveillance programme of the workers shall be undertaken periodically to observe any contractions due to exposure to dust and to take corrective measures, if needed and records maintained thereof. The quality of environment due to outsourcing and the health and safety issues of the outsourced manpower should be addressed by the company while outsourcing.	The occupational health surveillance programme of the workers is done regularly by our Occupational Health Department, Tata Central Hospital, Jamadoba. We have a PME (Periodic Medical Examination) centre approved by DGMS where annually 20% of the workers identified from workforce engaged in active mining operations are subjected to full medical checkup including hearing impairment checkup, etc. These results are regularly submitted to DGMS as per mines rules. Contractual workers health examination is also done by PME centre.
(xi)	A separate environmental management cell with suitable qualified personnel shall be set up under the control of a Senior Executive, who will report directly to the Head of the company.	We have a separate Environmental Management Cell with two qualified personnel. (One Head and one Senior Manager). The reporting of Environmental Cell is directly to General Manager of the Division.
(xii)	The funds earmarked for environmental protection measures shall be kept in separate account and shall not be diverted for other purpose. Year-wise expenditure shall be reported to this Ministry and its Regional Office at Bhubaneswar.	The Environment Cell has a separate fund for Environmental protection measures and for complying with legal requirements. The annual environmental expenditure for the financial year 2016-17 is Rs. 96.31 lakhs. The details are given below-

		S. No.	Environment Management Activity	Expenditure in Lakhs
		1.	Tailings Management System	6
		2.	Dust suppression system	3
		- 3.	Housekeeping measures includes removing spillage, improvement of roads	12
		4.	Spillage control measures	2
		5.	Mechanical dewatering system	29
		6.	Water spraying on roads for dust control	20
		7.	Chemical Dewatering	5
		8.	Horticultural activities including green belt development and regular lawn and garden maintenance	16.46
		9.	Plantation of saplings and maintenance	2.85
			Total Cost incurred	96.31
xiii)	which shall be in the vernacular language of the locality concerned within seven days of the clearance letter informing that the project has been accorded environmental clearance and a copy of the clearance letter is available with the State Pollution control Board and may also be seen at the website of the ministry of Environment & Forests at http://envfor.nic.in .			
xiv)	A copy of the environmental clearance letter shall be marked to concerned Panchayat/Zila Parishad, Municipal Corporation or Urban Local Body and local NGO, if any, from whom any suggestion/representation has been received while processing the proposal. A copy of the clearance letter shall also be displayed on the company's website.		been complied with.	8
(xv)	A copy of the clearance letter shall be displayed on the website of the concerned State Pollution Control Board. The EC letter shall also be displayed at the Regional Office, District Industry Centre	It has	been complied with.	

	and Collector's Office/Tehsildar's Office for 30 days.	
(xvi)	The clearance letter shall be uploaded on the company's website. The compliance status of the stipulated EC conditions shall also be uploaded by the project authorities on their website and updated at least once every six months so as to bring the same in the public domain. The monitoring data of environmental quality parameters (air, water, noise and soil) and critical pollutants such as PM10, PM2.5, SO2 and NOx (ambient and stack if any) and critical sectoral parameters shall also be displayed at the entrance of the project premises and mines office and in corporate office and on the company's website.	The clearance letter has been uploaded on the company's website. The compliance status (as Half-yearly compliance report) is being uploaded in company's website (Enclosed as Annexure-III). The display of information near the washery's office has been provided.
(xvii)	The project proponent shall submit six monthly reports on the status of compliance of the stipulated environmental clearance conditions (both in hard copy and in e-mail) to the respective Regional Office of the MOEF, the respective Zonal offices of CPCB and the SPCB.	It has been complied with.
(xviii)	The Regional Office of this Ministry located at Bhopal shall monitor compliance of the stipulated conditions. The Project authorities shall extend full cooperation to the office(s) of the Regional Office by furnishing the requisite data/ information/monitoring reports.	It will be complied with.

The environmental statement for each financial year ending 31st March in Form-V is mandated to be submitted by the project proponent tot the concerned State Pollution Control Board as prescribed under the linvironment (Protection) Rules, 1986, as amended subsequently, shall also be uploaded on the company's website along with the status of compliance of EC conditions and shall be sent to the respective Regional Offices of the MOEF by E-mail.

(xix)

The environmental statement for financial year 2016-17 has been submitted to JSPCB on 26th September 2017 and it is also uploaded on the company website (Annexure-III). The soft copy of Environment Statement is also sent to MOEF by email at rotranchi-meffalgov.in.

General Minager Coal

AIR QUALITY REPORT

Core zone & Buffer zone

Period- April'17 to June'17

No. of sampling points: 4

Location	Latitude/ Longitude	Date	Weather Condition	SPM 24 Hourly Limit- 700 µg/m³	RSPM 24 Hourly Limit- 300 µg/m ³	SO ₂ 24 Hourly Limit- 120 µg/m ³	NOx 24 Hourly Limit- 120 µg/m ³
		04.04.17	Clear	156.9	8.69	13.9	11.2
Jamadoba Group Office	23°42′15.3″ N/ 86°24′11″ E	03.05.17	Clear	148.9	72.1	14.5	13.2
		05.06.17	Clear	132.9	58.7	8.9	11.2
		Buffer zone (a	is per NAAQS 2	Buffer zone (as per NAAQS 2009 for ambient air quality standards)	nality standards)		
Location	Latitude/ Longitude	Date	Weather Condition	PM10 24 Hourly Limit- 100µg/m³	PM2.5 24 Hourly Limit- 60µg/m³	SO ₂ 24 Hourly Limit- 80µg/m ³	NO ₂ 24 Hourly Limit- 80µg/m ³
		19.04.17	Clear	8.68	38.7	7.6	10.8
Digwadih 12 No.	23°41'42" N/ 86°24'45 3" E	15.05.17	Clear	84.3	41.3	9.8	12.1
(mar)		12.06.17	Clear	82.1	43.2	7.2	10.1
12		13.04.17	Clear	85.4	51.1	8.4	11.4
New Village Colony, Jamadoba	23°41'51" N/ 86°23'19" E	18.05.17	Clear	78.9	52.2	10.2	8.7
		14.06.17	Clear	77.9	39.8	8.1	8.3
	3	27.04.17	Clear	77.1	33.5	7.8	8.9
6&7 Pits Kalimandir colony	23°43'15" N/ 86°24'12" E	22.05.17	Clear	83.2	44.5	9.2	10.1
		21.06.17	Rainy	81.8	46.1	8.2	9.3

AIR QUALITY REPORT

Core zone & Buffer zone

Period- July'17 to September'17

No. of sampling points: 4

	Ō	Core zone (as per Ai	ir quality standa	Air quality standards for coal mines in EPA Notification, 1988)	PA Notification, 198	(88)	
Location	Latitude/ Longitude	Date	Weather Condition	SPM 24 Hourly Limit- 700 µg/m³	RSPM 24 Hourly Limit- 300 µg/m ³	SO ₂ 24 Hourly Limit- 120 µg/m³	NOx 24 Hourly Limit- 120 µg/m³
(2) (3) (4)		03.07.17	Cloudy	112.3	45.3	7.5	8.1
Jamadoba Group Office	23°42'15.3" N/ 86°24'11" E	02.08.17	Cloudy	128.5	53.4	7.6	8.3
		04.09.17	Clear	132.7	64.4	10.8	7.6
		Buffer zone (a	is per NAAQS 20	(as per NAAQS 2009 for ambient air quality standards)	nality standards)		
Location	Latitude/ Longitude	Date	Weather	PM10 24 Hourly Limit- 100µg/m ³	PM2.5 24 Hourly Limit- 60µg/m ³	SO ₂ 24 Hourly Limit- 80μg/m³	NO ₂ 24 Hourly Limit- 80µg/m ³
1	9	10.07.17	Rainy	71.2	35.4	8.1	9.2
Digwadih 12 No.	23°41'42" N/ 86°24'45 3" E	09.08.17	Clear	78.4	43.2	8.9	8.1
(mara)		06.09.17	Clear	91.2	48.7	9.2	9.9
		13.07.17	Clear	61.3	31.1	6.2	7.1
New Village Colony, Ismadoba	23°41'51" N/ 86°23'19" F	16.08.17	Rainy	76.5	41.8	7.6	6.4
		14.09.17	Rainy	71.2	42.2	8.2	7.7
		17.07.17	Clear	72.2	34.4	7.1	6.3
6&7 Pits Kalimandir	23°43'15" N/ 86°24'12" F	24.08.17	Clear	71.1	38.9	8.1	8.2
		22.09.17	Clear	82.3	39.9	10.2	9.2

10

Ground Water Quality Analysis (Hand Pump & Dugwell) Pre-Monsoon Season- May 2017

S.No Date Location Time Depth in meter (m) pH Conductivity,						San	Sample Parameter	
15.05.17 Purnadih (Jorapokhar) 12.20PM 8.82 6.9 784 15.05.17 Bhowra 13 No 11:45AM 3.05 7.2 552 15.05.17 Mohalbani Basti 11:15AM 9.15 6.9 440 15.05.17 Digwadih 12 No 10:55AM 8.20 6.9 440 15.05.17 Digwadih 10 No F & J 10:30AM 4.05 7.0 490 15.05.17 Kalimela Shivmandir 09:10AM 2.15 7.0 602 15.05.17 Kalimela Kalimandir 09:15AM 7.85 7.2 448 15.05.17 Lower Dungari 12:40PM 7.85 7.2 448 15.05.17 Loper Dungari 12:55PM 7.10 7.0 564 15.05.17 Kenduadih Basti 01:40AM 3.15 6.8 536 15.05.17 Kenduadih Basti 01:40AM 3.15 6.9 6.9 6.9 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 564	S.No	Date	Location	Time	Depth in meter (m)	Hd	Electrical Conductivity,	Total Hardness (as CaCO ₃), mg/l
15.05.17 Bhowra 13 No 11:45AM 3.05 7.2 552 15.05.17 Mohalbani Basti 11:15AM 9.15 6.9 440 15.05.17 Digwadih 12 No 10:55AM 8.20 6.9 470 15.05.17 Digwadih 10 No F & J 10:30AM 2.15 7.0 490 15.05.17 Kalimela Kalimandir 09:15AM 2.15 7.0 602 15.05.17 Lower Dungari 12:40PM 7.85 7.2 448 15.05.17 Upper Dungari 12:55PM 5.55 7.2 456 15.05.17 Pattia Basti 01:15PM 7.10 7.0 564 15.05.17 Kenduadih Basti 01:40AM 3.15 6.8 536 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 584 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 584 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 584 15.05.17 J		15.05.17	Purnadih (Jorapokhar)	12:20PM	8.82	6.9	784	899
15.05.17 Mohalbani Basti 11:15AM 9.15 6.9 440 15.05.17 Digwadih 12 No 10:55AM 8.20 6.9 372 15.05.17 Digwadih 10 No F & J 10:30AM 4.05 7.0 490 15.05.17 Kalimela Shivmandir 09:10AM 2.15 7.0 602 15.05.17 Kalimela Kalimandir 09:15AM 7.85 7.2 448 15.05.17 Lower Dungari 12:40PM 7.85 7.2 448 15.05.17 Upper Dungari 12:55PM 5.55 7.2 456 15.05.17 Pattia Basti 01:15PM 7.10 7.0 564 15.05.17 Kenduadih Basti 01:40AM 3.15 6.9 68 684 15.05.17 Jorapokhar Kushtand 12:10PM 3.60 7.0 584 15.05.1 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 512 7.2 15.05.17 G& Pits (Ayodhya Nagri) 02:10PM 4.95 <td< td=""><td>7</td><td>15.05.17</td><td>Bhowra 13 No</td><td>11:45AM</td><td>3.05</td><td>7.2</td><td>552</td><td>514</td></td<>	7	15.05.17	Bhowra 13 No	11:45AM	3.05	7.2	552	514
15.05.17 Digwadih 12 No 10:55AM 8.20 6.9 372 15.05.17 Digwadih 10 No F & J 10:30AM 4.05 7.0 490 15.05.17 Kalimela Shivmandir 09:10AM 2.15 7.0 602 15.05.17 Kalimela Kalimandir 09:15AM 7.85 7.2 448 15.05.17 Lower Dungari 12:40PM 7.85 7.2 456 15.05.17 Upper Dungari 12:55PM 5.55 7.2 456 15.05.17 Pattia Basti 01:15PM 7.10 7.0 564 15.05.17 Kenduadih Basti 01:40AM 3.15 6.8 536 15.05.17 Jorapokhar Kushtand 12:10PM 4.95 6.9 6.9 684 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 588 15.05.17 Jamadoba Nagri 02:10PM 4.90 7.1 512	3	15.05.17	Mohalbani Basti	11:15AM	9.15	6.9	440	426
15.05.17 Digwadih 10 No F & J 10:30AM 4.05 7.0 490 15.05.17 Kalimela Shivmandir 09:10AM 2.15 7.0 602 15.05.17 Kalimela Kalimandir 09:15AM 3.75 6.9 616 15.05.17 Lower Dungari 12:40PM 7.85 7.2 448 15.05.17 Upper Dungari 12:55PM 5.55 7.2 456 15.05.17 Renduadih Basti 01:15PM 7.10 564 564 15.05.17 Kenduadih Basti 01:40AM 3.15 6.9 684 536 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 588 588 15.05.17 Jamadoba 3 No 10:00AM 4.90 7.1 512 512	4	15.05.17	Digwadih 12 No	10:55AM	8.20	6.9	372	340
15.05.17 Kalimela Shivmandir 09:10AM 2.15 7.0 602 15.05.17 Kalimela Kalimandir 09:15AM 3.75 6.9 616 15.05.17 Lower Dungari 12:40PM 7.85 7.2 448 15.05.17 Upper Dungari 12:55PM 5.55 7.2 456 15.05.17 Pattia Basti 01:15PM 7.10 7.0 564 15.05.17 Kenduadih Basti 01:40AM 3.15 6.8 536 15.05.17 Jorapokhar Kushtand 12:10PM 4.95 6.9 684 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 588 15.05.17 6&7 Pits (Ayodhya Nagri) 02:10PM 4.90 7.1 512	5	15.05.17	Digwadih 10 No F & J	10:30AM	4.05	7.0	490	384
15.05.17 Kalimela Kalimandir 09:15AM 3.75 6.9 616 15.05.17 Lower Dungari 12:40PM 7.85 7.2 448 15.05.17 Upper Dungari 12:55PM 5.55 7.2 456 15.05.17 Pattia Basti 01:15PM 7.10 7.0 564 15.05.17 Kenduadih Basti 01:40AM 3.15 6.8 536 15.05.17 Jamadoba 3 No 12:10PM 4.95 6.9 684 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 588 15.05.17 6&7 Pits (Ayodhya Nagri) 02:10PM 4.90 7.1 512	9	15.05.17	Kalimela Shivmandir	09:10AM	2.15	7.0	602	532
15.05.17 Lower Dungari 12:40PM 7.85 7.2 448 15.05.17 Upper Dungari 12:55PM 5.55 7.0 456 15.05.17 Pattia Basti 01:15PM 7.10 7.0 564 15.05.17 Kenduadih Basti 01:40AM 3.15 6.8 536 15.05.17 Jorapokhar Kushtand 12:10PM 4.95 6.9 684 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 588 15.05.17 6&7 Pits (Ayodhya Nagri) 02:10PM 4.90 7.1 512	7	15.05.17	Kalimela Kalimandir	09:15AM	3.75	6.9	616	546
15.05.17 Upper Dungari 12:55PM 5.55 7.2 456 15.05.17 Pattia Basti 01:15PM 7.10 7.0 564 564 15.05.17 Kenduadih Basti 01:40AM 3.15 6.8 536 536 15.05.17 Jorapokhar Kushtand 12:10PM 4.95 6.9 684 588 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 588 588 15.05.17 6&7 Pits (Ayodhya Nagri) 02:10PM 4.90 7.1 512 7.1	8	15.05.17	Lower Dungari	12:40PM	7.85	7.2	448	392
15.05.17 Pattia Basti 01:15PM 7.10 7.0 564 15.05.17 Kenduadih Basti 01:40AM 3.15 6.8 536 15.05.17 Jorapokhar Kushtand 12:10PM 4.95 6.9 684 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 588 15.05.17 6&7 Pits (Ayodhya Nagri) 02:10PM 4.90 7.1 512	6	15.05.17	Upper Dungari	12:55PM	5.55	7.2	456	984
15.05.17 Kenduadih Basti 01:40AM 3.15 6.8 536 15.05.17 Jorapokhar Kushtand 12:10PM 4.95 6.9 684 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 588 15.05.17 6&7 Pits (Ayodhya Nagri) 02:10PM 4.90 7.1 512	10	15.05.17	Pattia Basti	01:15PM	7.10	7.0	564	478
15.05.17 Jorapokhar Kushtand 12:10PM 4.95 6.9 684 15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 588 15.05.17 6&7 Pits (Ayodhya Nagri) 02:10PM 4.90 7.1 512	11	15.05.17	Kenduadih Basti	01:40AM	3.15	8.9	536	442
15.05.17 Jamadoba 3 No 10:00AM 3.60 7.0 588 15.05.17 6&7 Pits (Ayodhya Nagri) 02:10PM 4.90 7.1 512	12	15.05.17	Jorapokhar Kushtand	12:10PM	4.95	6.9	684	528
15.05.17 6&7 Pits (Ayodhya Nagri) 02:10PM 4.90 7.1 512	13	15.05.17	Jamadoba 3 No	10:00AM	3.60	7.0	588	490
	14	15.05.17	6&7 Pits (Ayodhya Nagri)	02:10PM	4.90	7.1	512	482

Ground Water Quality Analysis (Hand Pump & Dugwell) Monsoon Season- August 2017

					Sar	Sample Parameter	
S.No	Date	Location	Time	Depth in meter (m)	Hd	Electrical Conductivity, µS/m	Total Hardness (as CaCO ₃), mg/l
1	31.08.17	Purnadih (Jorapokhar)	10.35AM	1.43	4.2	752	734
2	31.08.17	Bhowra 13 No	10.45AM	1.52	7.2	969	562
3	31.08.17	Mohalbani Basti	11.05AM	1.87	7.0	708	889
4	31.08.17	Digwadih 12 No	11.15AM	1.83	7.1	499	458
5	31.08.17	Digwadih 10 No F & J	11.25AM	2.83	7.2	886	812
9	31.08.17	Kalimela Shivmandir	12.05PM	96.0	7.0	744	989
7	31.08.17	Kalimela Kalimandir	12.10PM	1.02	7.3	904	848
00	31.08.17	Lower Dungari	12.25PM	2.14	7.0	614	580
6	31.08.17	Upper Dungari	12.40PM	1.64	7.1	628	969
10	31.08.17	Pattia Basti	12.55PM	1.96	7.1	592	572
11	31.08.17	Kenduadih Basti	1.05PM	1.12	7.2	776	752
12	31.08.17	Jorapokhar Kushtand	10.20AM	2.28	7.0	857	794
13	31.08.17	Jamadoba 3 No	1.35PM	1.24	7.2	804	782
14	31.08.17	6&7 Pits (Ayodhya Nagri)	1.20PM	1.74	7.2	889	614

S.S.Environics (India) Pvt. Ltd. (An ISO 9001:2008, 14001:2004 and OHSAS 18001:2007 Certified Company)

Plot No-361/2314 "Sustenance Tower"

At: Patrapada, P.O: Dumuduma, Dist: Khurda, Bhubaneswar-751 019, Odisha

Tele Fax: 0674- 2471574; E-mail: emails@ssenvironics.com

4

S

12

-

Ref No: SSE/17/R-0562

AMBIENT AIR QUALITY REPORTS

Month of Monitoring Name of Industry

No.

Name of the

: May 2017

: M/s. Tata Steel Ltd, Jharia division, Jamadoba Jharkhand

TVG

nics (India) Pvt. Ltd

BDL Values:

Method of Analysis & Code of Method Tatasteel Officer's Colony Digwadih Near General Manager's Office Central Workshop Area Jamadoba Jamadoba Colliery CPCB Standard NH₃:- 20 µg/m³ PM-10:-5μg/m³ PM-2.5:- 2.0μg/m³ SO₂:- 4 μg/m³, NO_X:- 9 30,05,17 29.05.17 29.05.17 30.05.17 Date of Time Weighted Average 24hrly 24hrly 24hrly 24hrly 24hrly ND: Not Detected PM₁₀ (μg/m³) Gravimetric Method 75.60 100 .50 IS: 5182, Part-23 PM2.5 (µg/m³) Gravimetric Method 44.7 32.5 39.2 60 IS: 5182, Part-23 Improved West-Gaeke Method (F.G.) 5.7 5.7 4.4 80 1S: 5182, Part-2 µg/m³, CO:- 0.1 mg/m³, Ozone:- 5 µg/m³, Modified Jacob & Hochheiser (Na. 13.9 13.6 13.1 80 Arsenite) IS: 5182.Part-6 Non Dispersive Infrared 4(1hr) 0.34 0.28 mg/00 Spectroscopy (NDIR) IS: 5182, Part-10 1. Chemiluminescence 25.1 33.4 m (mg NH 400 2.Idophenol Blue Method APHA-401 1. Chemiluminescence 180 (1hr) 8.1 6.4 8.6 7.7 2.Chemical Method 1S: 5182, Part-9 Ni - 0.05 ICP Method After Sampling on BDL BDL BDI m³) 1 EPM 2000 OR Equivalent Filter ICP Method After Sampling on BDI BDI 21 1 1.6 EPM 2000 OR Equivalent Filter As:- 0.05 ng/m ICP Method After Sampling on ii_(iiii Cd ND B 3 B 1 EPM 2000 OR Equivalent Filter ICP Method After Sampling on 13 (B) C B B B Ð 1 EPM 2000 OR Equivalent Filter

Annexure-III

Upload of compliance report on company's website





TATA STEEL



ENVIRONMENTAL POLICY

Tata Steel's environmental responsibilities are driven by our commitment to preserve the environment and are integral to the way we do business.

- 1. We are committed to deal proactively with Climate Change issue by efficient use of natural resources & energy; reducing and preventing pollution; promoting waste avoidance and recycling measures; and product stewardship.
- We shall identify, assess and manage our environment impact.
- We shall regularly monitor, review and report publicly our environmental performance.
- We shall develop & rehabilitate abandoned sites through afforestation and landscaping and shall protect and preserve the biodiversity in the areas of our operations.
- We shall enhance awareness, skill and competence of our employees and contractors so as to enable them to demonstrate their involvement, responsibility and accountability for sound environmental performance.
- 2. We are committed to continual improvement in our environmental performance.
- We shall set objective-targets, develop, implement and maintain management standards and systems, and go beyond compliance of the relevant industry standards, legal and other requirements.
- 3. We will truly succeed when we sustain our environmental achievement and are valued by the communities in which we work.

Date: November 1, 2013

T V Narendran Managing Director

Jamadoba Coal Washery- Ash% and Quantity of raw coal and products (Apr-17 to Oct-17)

Parameter	Item		Apr.17	May'17	Jun'17	Jul'17	Aug'17	Sept'17	Oct'17
	Raw Coal		36.46%	36.05%	36.46%	34.64%	35.78%	34.84%	36.95%
	Clean Coal		18.15%	18.51%	18.15%	18.43%	18.54%	18.60%	18.59%
Ash (%)	Two Product Rejects	t Rejects	53.71%	56.01%	53.71%	59.64%	60.20%	59.65%	59.38%
	Tailings	And the second s	40.93%	42.46%	40.93%	43.55%	42.93%	42.71%	46.01%
Ouantity	Raw coal received	seived	58804	61037	59865	78990	80645	73739	63055
(Tonnage)	Raw coal T'put	out	57614	61607	59346	77660	81507	73545	62972
	Clean coal production	roduction	24325	25736	26675	40644	41375	38020	30932
	Clean coal	JSR	11750	15762	27142	39680	40245	39888	27342
	dispatch	HMC	11568	7915	3867	0	0	0	3480
	2 PR Production	tion	22626	26223	20936	22770	21885	21695	18131
	2 PR dispatch	4	8567	22044	12813	17704	35907	14891	23482
	Tailings Production	duction	12331	14794	14382	17653	21876	17106	16800
	Tailings Dispatch	oatch	5959	11535	7703	4247	8893	15787	14989

